LA-UR-23-20396

Approved for public release; distribution is unlimited.

Title: Gas Liberation, Detection, & Quantification from Geological,

Experimental, & Nuclear Weapons Test Materials

Author(s): Eldridge, Daniel Lee

Miller, Hayden Bryce Dutcher

Rahn, Thomas A.

Campe, Christopher Edward

Migdissov, Artaches Boukhalfa, Hakim

Intended for: Report

Issued: 2023-01-17









Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher dientify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



Gas Liberation, Detection, & Quantification From Geological, Experimental, & Nuclear Weapons Test Materials

Hayden Miller* (Part 1); Daniel Eldridge* (Part 2); Thom Rahn

Christopher Campe; Artaches Migdissov; Hakim Boukhalfa

*Presenting Authors

01-17-2023

LA-UR-23-#####





Part 1 Hayden Miller



Overview of Accomplishments

Task: Establish new capabilities to liberate and quantify gases from test-site materials, including stable isotope measurements on targeted gases

Accomplishments:

- Designed, built, tested, and established crush/gas purification line
- Developed calibration methodology via calibrated volume (Pettit & Schaller, 2019)
- Successfully applied our methodology to analog and experimental materials:
 - Demonstrated gas liberation and quantification from analog geologic (Soda Dam carbonate, trinitite aerobeads) and experimental materials
 - Demonstrated the measurement feasibility of stable isotope analysis of target gas (CO₂) obtained from a crushed material



Refurbished Laboratory Space in the GGRL

New Crushing and Gas Extraction/Purification Capabilities






Custom Vacuum Line for Gas Liberation, Quantification, & Purification






Custom Vacuum Line for Gas Liberation, Quantification, & Purification





QMS Noble Gas Quantification: Krypton Stable Isotopes

Sample size: 0.2 to 2 nanomoles (10⁻⁹) pure Kr gas



Preliminary External Reproducibility (1 σ ; n = 5)

⁸⁰Kr: ± 0.13%

82Kr: ± 0.15%

83Kr: ± 0.16%


84Kr: ± 0.49%

86Kr: ± 0.10%



QMS Noble Gas Quantification: Xenon Stable Isotopes

Sample size: ~3 nanomoles (10⁻⁹) pure Xe gas



Preliminary External Reproducibility (1 σ ; n = 3)

¹²⁴Xe: ± 0.02%

 126 Xe: ± 0.02%

 128 Xe: ± 0.04%

 129 Xe: ± 0.02%

 130 Xe: ± 0.02%

 131 Xe: ± 0.02%

 132 Xe: ± 0.06%

 134 Xe: $\pm 0.03\%$

 136 Xe: ± 0.01%



Part 2 Daniel Eldridge



Crush Tests:

Demonstrating New Capability Development

Crush Test 1:

Analog materials (Soda Dam Carbonate, ~300mg)

- Quantified gas composition by QMS (e.g., CO₂/N₂ ratio)
- Determined Carbon-13 isotope composition of liberated CO₂ by IRMS

Crush Test 2:

Experimental silicate melt glass containing two-phase inclusions (gas, agueous fluid)

Detected organic volatiles (contaminant) that inform ongoing experiments

Crush Test 3:

Trinitite aerobead (~100mg)

Detected gas signature unique to formation (fireball) environment




Crush Test 1: Local Soda Dam Carbonate (304 mg)

Background-corrected peaks at given m/z (e.g., N₂ and CO₂ quantification)



Soda Dam Carbonate Fragment


Measurements of Gas from Crush on Quadrupole MS






Crush Test 1: Local Soda Dam Carbonate (304 mg)

Localized 3-Point Calibration Based on Standard Gas






$$\frac{CO_2}{N_2} = 0.20 \pm 0.02 \text{ (1 s.e.)} \approx 400 \times Air$$



Crush Test 1: Local Soda Dam Carbonate (304 mg)


Stable Isotope Measurement (Carbon-13) of Crush-Liberated CO₂(g)







Crush Test 2: Experimental Silicate Melt

NaAlSi₃O₈-KAlSi₃O₈-SiO₂ System (haplogranite), H₂O-saturated, ~700°C Successfully generated melt glass with two-phase inclusions (aqueous fluid + gas)



Experiments conducted by DR team-members: Chris Campe (post-Masters student), Artaches Migdissov, Hakim Boukhalfa








Crush Test 2: Experimental Silicate Melt


Mass spectrum of liberated gases from crush






Crush Test 2: Experimental Silicate Melt

Identified organic contaminant in experiment (informs mitigation strategies in ongoing/future experiments)






Crush Test 3: Trinitite Aerobead (~100 mg)




National Park Service https://www.nps.gov/whsa/learn/historyculture/trinity-site.htm



Crush Test 3: Trinitite Aerobead (~100 mg)







Summary/Future

Accomplishments: Capability Development COMPLETE

- Developed and demonstrated capability for crushing materials and liberating volatiles (including trinitite).
- Demonstrated the ability to quantify (QMS) and perform stable isotope measurements (IRMS) on liberated gases.

Next steps: Measure Samples (~6 months) and Write-Up (~2 months)

- Expand measurements to more trinitite samples for open literature publication:
 - Aerobead vs. on-the-ground samples
 - Gas quantification + volatile metal isotope analysis on crushed material (e.g., Cs, Zn)
- Apply methodology to underground test materials.

